



Gromax Enterprises Corp.

17335 Daimler Street, Irvine, CA 92614
Toll: 800-343-3508 Tel: 949-833-1199 Fax: 949-833-0099
www.gromaxchemical.com e-mail: info@gromax-usa.com

OZ-100 **Flow Promoter**

Introduction:

GYC GROUP is the leading manufacturer of specialty chemicals in Asia.

We devote ourselves to supplying products and solutions to our customers to satisfy and expand the market needs.

OZ-110S is a comprehensive lubricant and dispersing coupling additive that provides dispersibility and lubricity to resin and plastic during production.

It can be widely used in the injection, extrusion, compounding process.

Properties

GRADE	OZ-110S
Appearance	White solid
Bulk specific gravity	0.5-0.6
Lubricity	Good

Features/Benefits

- Excellent fluid modifying agent
- Good stability and high formability
- Good lubricity
- Improve flow promotion of plastic and resin
- Heat stability
- Suitable for extrusion, injection molding, spinning, granulation process.
- Outstanding lubricity and anti-adhesion ability °
- Good demolding effect for thermosetting resin and thermoplastic plastic
- Can be used in polymerization or compound process
- OZ-110S is suitable for transparent products
- Prevent blockage of tube, increase the added-value when manufacturing

Applications

- Thermosetting resin and thermoplastic plastic
- Olefins : PP, PE,HDPE, LDPE, EVA, POE
- Engineering plastic Nylon,: PBT,PET,PC,PA, POM, ABS,
- PVC
- Elastomer
- Styrene resin
- Extrusion, injection, film application

Adding

Recommended adding rate: 0.5%~2%

The adding rate is to be regarded as general guideline which can be adjusted according to the performance requirements.

Packing

20KG/bag

Storage

Store in a cool, dry, and well-ventilated place. Keep away from fire and avoid direct sunlight or damp. Seal tightly after use.

