

[在此鍵入]



Gromax Enterprises Corp.

17335 Daimler Street, Irvine , CA 92614

Toll: 800-343-3508 Tel: 949-833-1199 Fax: 949-833-0099

www.gromaxchemical.com e-mail: info@gromax-usa.com

Product	Product Characteristic	Resin System	Example of End-Product Application
473	Compatible with most nylon	PA6 / PA66 /	Plastic chairs, Motorcycle cases, Roller skate wheels
173H/173Y	Hydrolysis resistance	PA46	Radiator grilles, Thermal insulation
492	Used with nylon & PET	PA / PET	Containers, Electrical components
183E/435N/536K	Most suitable for PBT resin system	PBT / PET	Electrical switches, Computer fans, PET bottles, Connectors, Headlight cases
144A	Coupled & uncoupled PP(202P is integrity modified for 144A)	PP	Bumpers, Pump cases, Headlight cases
202P			
483	ABS application	ABS	Electrical components
183F			
301P	POM application	POM	Gears, Electrical components, Office equipment
473A	Designed for Polycarbonate resin	PC	Cell phones, TFT-LCD's and Digital Video cases
475	High temp. resin system	LCP / PPS / PS / PVC	Cell phone cases, Motherboard connectors
101C	Designed for a wide variety of BMC	UP / Phenolic / Epoxy	Building construction materials, Transformers, Decorations
152A	Suited for both injection-molded & compression-molded BMC (High Solubility)		
405/405D	Phenolic friction application	UP / Phenolic	Break pads, Decorations